



STANDALONE FORMING MACHINE

● Mechanical engineering

● Realizations

○ Cabling

○ Machines

This molding machine serves as a mold for encasing a polyurethane-insulated tank (such as a water heater tank).

The operator positions the tank (with the plug in place) on three pins at the base of the fixed half-shell.

He manually closes the pivoting half-shell.

He lowers the lid using a crank located at the rear.

Next, they secure the components using several clamping clamps to ensure a tight seal.

Then they inject the mixture through a port provided for this purpose.

After the polyurethane has cured, the operator opens the mold half to remove the insulated tank.

FEATURES:

- Height = 2170 mm
 - Width = 1800 mm
 - Depth = 1500 mm
 - Weight = 700 kg
 - Tank diameter = 650 mm
-
- Tank height = 1700 mm



CEREST

20 Rue des Frères Lumière
68000 Colmar - FRANCE



EMAIL

cerest@cerest.com






PHONE

+33 (0)3.89.21.02.56



INTERNET

www.cerest.com



Reference : 3878

Project added the 11/05/26



CEREST

20 Rue des Frères Lumière
68000 Colmar - FRANCE



EMAIL

cerest@cerest.com



PHONE

+33 (0)3.89.21.02.56



INTERNET

www.cerest.com